

UNO

Single channel, power monitor



NOW AVAILABLE

W/dBm

You can toggle your display between Watts or dBm units

KEY FEATURES

- ▶ **READS ALL POWER DETECTORS**
Thermopiles and photodetectors of the PH Series
- ▶ **LARGE LCD DISPLAY**
 - 76 x 57 mm
 - 32 mm digits
- ▶ **UNIQUE ERGONOMIC DESIGN**
Great for both handheld and tabletop use
- ▶ **ACCURATE**
24 bit A/D converter for high resolution measurements
- ▶ **SINGLE-BUTTON NAVIGATION**
Direct access and long press access to all the functions
- ▶ **EXTREMELY LOW CONSUMPTION**
Lasts 670 hours with 4 AA alkaline batteries
- ▶ **ECONOMICAL**
Get the best value for your money with this inexpensive and simple to use power monitor

ACCESSORIES



Optional 9V power supply



Wall support



Pelican carrying case

UNO

Specifications

CE NIST*
Traceable



*Also traceable to NRC-CNRC



UNO

DETECTOR TYPES Thermopiles, photodetectors (PH series)

DISPLAY LCD

POWER METER SPECIFICATIONS

Power range	10 nW to 10 kW
Thermopile	Single wide range scale
Photodetector	Autoscale
Digital resolution	
PH series	1 pW
XLP series	1 µW
UP series	1 mW
Monitor accuracy	±1%
Response time	1 s

DETECTOR COMPATIBILITY

Thermopiles	Average power (W, dBm)
Photodetectors	Average power (W, dBm)

GENERAL SPECIFICATIONS

Digital display size	76 x 57 mm LCD
Digit height	32 mm
Digit type	High contrast fields
Data display	Real-time
Dimensions (without stand)	210W x 122H x 44D mm
Weight (with batteries)	0.47 kg
Battery type	4 x AA alkaline
Battery life (estimated)	670 hours with detector
External power supply (optional)	100/240 VAC 50 - 60 Hz to 9 VDC 1.66 A

ORDERING INFORMATION

Product page



Specifications are subject to change without notice