SHEAUMANN





# T Series TO-Can 785nm 300mW

Single-mode, Continuous Wave (C)

300mW

Max

25 50

Тур

-20

۱	C	v	v	J

**Absolute Maximum Ratings** 

Parameter

Operational Temperature\*\*\*

Optical	Electrical	Characteristics	**
	Daram	otor	

Parameter	Unit	Тур	Max
Wavelength	nm	785	-
Operating Power	mW	300	-
Operating Current*	mA	395	450
Operating Voltage	V	1.9	2.2
Threshold Current	mA	65	85
Slope Efficiency	W/A	0.9	-
Vertical Far Field @FWHM	deg <sup>o</sup>	25	-
Horizontal Far Field @FWHM	deg <sup>o</sup>	8	-



## 9mm (M9T) M9T-785-0300-R5P **Features** &Options

- AIN Carrier on CU submount
- AuSn Bonding
- Hermetically sealed package
- AR Coated window
- **Optional Photodiode**
- **Optional Microlens**

This datasheet is for general reference only. Specifications are subject to change without notice. Product subject to availability. Visit sheaumann.com or contact sales@sheaumann.com for more information on products and services.

Unit Condition Min

°C CW

Safety Warning Laser light emitted from any laser diode is invisible and may be harmful to the human eye. Avoid looking directly into the laser aperture when the device is in operation. The use of optical instruments with this product will increase eye hazard.

Please note that CW lasers may be damaged by excessive drive current or switching transients
Data is based on CW operation at 25<sup>o</sup>C.
<sup>on</sup> Device degradation accelerates with increased temperature.

The primary cause of diode failure is unexpected electrostatic discharge. To help prevent device failures, the user should always wear an ESD wrist strap, ground all applicable work surfaces and follow anti-static techniques when handling diode lasers.

Operation Consideration Operating the laser beyond the limits of the provided specifications may result in device failure or a safety hazard and will void warranty. Devices must be passively or actively cooled in accordance with the provided specifications. Failure to comply with heatsinking requirements may result in device failure.

Warranty Due to the delicate nature of laser diodes, Sheaumann offers a limited warranty for all products. Please refer to our Terms and Conditions for full details.

#### Compliance Notice

These products are inteended solely as a component of an electronic product and are not certified in accordance with IEC 60825-1 or 21 CFR 1040.10/21 CFR 1040.11. These products are subject to Export Administration Regulations (EAR) and will require a Destination Control Statement or End User Agreement for each sales order.



1

Germany and Other Countries Laser Components Germany GmbH Tel: +49 8142 2864-0 Fax: +49 8142 2864-11 info@lasercomponents.com www.lasercomponents.com

### France

Laser Components S.A.S. Tel: +33 1 39 59 52 25 Fax: +33 1 39 59 53 50 info@lasercomponents.fr www.lasercomponents.fr

### United Kingdom

Laser Components (UK) Ltd. Tel: +44 1245 491 499 Fax: +44 1245 491 801 info@lasercomponents.co.uk www.lasercomponents.co.uk

### Nordic Countries

Laser Components Nordic AB Tel: +46 31 703 71 73 Fax: +46 31 703 71 01 info@lasercomponents.se www.lasercomponents.se