



T Series TO-Can 852nm 300mW

Single-mode, Continuous Wave (CW)

300mW

Max

500

2.2

75

Тур

852

300

430

1.9

55

0.8 16 8

Optical Electrical Characteristics **

Optical Electrical Characteristics					
Parameter	Unit				
Wavelength	nm				
Operating Power	mW				
Operating Current*	mA				
Operating Voltage	V				
Threshold Current	mA				
Slope Efficiency	W/A				
Vertical Far Field @FWHM	deg ^o				
Horizontal Far Field @FWHM	deg ^o				

Absolute Maximum Ratings

Absolute Maximum Natings					
Parameter	Unit	Condition	Min	Тур	Max
Operational Temperature***	οС	CW	-20	25	50

* Please note that CW lasers may be damaged by excessive drive current or switching transients.

* Data is based on CW operation at 25°C.

** Device degradation accelerates with increased temperature.



9mm (M9T)

M9T-852-0300-R5P

Features &Options

- AIN Carrier on CU submount
- AuSn Bonding
- Hermetically sealed package
- AR Coated window
- Optional Photodiode
- **Optional Microlens**

This datasheet is for general reference only. Specifications are subject to change without notice. Product subject to

Safety Warning
Laser light emitted from any laser diode is invisible and may be harmful to the human eye. Avoid looking directly into the laser aperture when the device is in operation.
The use of optical instruments with this product will increase eye hazard.

CDU WARTING

The primary cause of diode failure is unexpected electrostatic discharge. To help prevent device failures, the user should always wear an ESD wrist strap, ground all applicable work surfaces and follow anti-static techniques when handling diode lasers.

Operation Consideration
Operating the laser beyond the limits of the provided specifications may result in device failure or a safety hazard and
will void warranty. Devices must be passively or actively cooled in accordance with the provided specifications. Failure
to comply with heatsinking requirements may result in device failure.

Warranty
Due to the delicate nature of laser diodes, Sheaumann offers a limited warranty for all products. Please refer to our
Terms and Conditions for full details.

Compinance Notice These products are intended solely as a component of an electronic product and are not certified in accordance with IEC 60825-1 or 21 CFR 1040.10/21 CFR 1040.11. These products are subject to Export Administration Regulations (EAR) and will require a Destination Control Statement or End User Agreement for each sales order.









Germany and Other Countries

Laser Components Germany GmbH Tel: +49 8142 2864-0 Fax: +49 8142 2864-11 info@lasercomponents.com www.lasercomponents.com

Laser Components S.A.S. Tel: +33 1 39 59 52 25 Fax: +33 1 39 59 53 50 info@lasercomponents.fr www.lasercomponents.fr

United Kingdom

Laser Components (UK) Ltd. Tel: +44 1245 491 499 Fax: +44 1245 491 801 info@lasercomponents.co.uk www.lasercomponents.co.uk Nordic Countries

Laser Components Nordic AB Tel: +46 31 703 71 73 Fax: +46 31 703 71 01 info@lasercomponents.se www.lasercomponents.se